

Berly Electronics Co., Ltd

Website: <http://www.blledlight.com>

Email: sales@blledlight.com admin@blledlight.com

PRODUCTS SPECIFICATION

3528 SMD LED FLEX STRIP

(Crystal series)

For LD-FL-C3528-12-120

Made by	Checked by	Version
Musitafa	Nautica Huang	2009.2.4

CE



ROHS



3528 SMD Flexible strip Introduction

Features:

Available in 12V DC maximum

Very bright & low power consumption

Operating temperature: -20 ° -50 °

Long life span LED lights , more than 50 ,000 hours + .


Adhesive back , peel & stick !

Dimmable to 6V DC.

Water-proof, IP67.


Applications:

Ideal for sign letters and channel letters, concealed lights, room lighting, equipment,





Assembly drawing


Top View



Section



5meter/reel



1 reel/bag



360X240X250mm

25bags/Box


View Angle: 120degrees

Operation Temperature: -20 ~ 50








Store Temperature: -30 ~ 80

Package: 5 meter strip in one reel, one reel in one anti-static bag, 25 bags put into one carton.


Crystal series :3528 120LED/Meter



This flexible strip is made of 3528 LED, the PCB holder is Crystal strip.

Crystal series:3528 120LED/meter							
Part number	Color	LED QTY/meter	Lumen/meter	Voltage	Power/meter	packing means	
LD-FL-C3528R-12-120	Red 	120	240	12	9.6 watt	5meter/reel	
LD-FL-C3528Y-12-120	Yellow 	120	240	12	9.6 watt	5meter/reel	
LD-FL-C3528B-12-120	Blue 	120	300	12	9.6 watt	5meter/reel	
LD-FL-C3528G-12-120	Green 	120	480	12	9.6 watt	5meter/reel	
LD-FL-C3528W-12-120	White 	120	780	12	9.6 watt	5meter/reel	
LD-FL-C3528WW-12-120	Warm White 	120	720	12	9.6 watt	5meter/reel	
LD-FL-C3528P-12-120	Pink 	120	240	12	9.6 watt	5meter/reel	

for: red, blue, green, yellow



for: white LED

How to connect Flexible strip

Below shows you how to connect the flexible strip to power supplies.

